



## ARD104AB21R/L

**Black**  
Model: ARD104AB21R/L



### FEATURES

- Quiet Operation
- Special Quick Chill 'N Snooze® Functions
- Full-Width Removable Shelf
- Fits Most Existing Absorption-Type Unit Cabinetry
- Door Beverage Can Dispenser

### PRODUCT SPECIFICATIONS

Energy	ENERGY STAR® Qualified - Tier I 242 KWH/Yr Energy Consumption 10% Less Energy than Federal Standard
Quick Chill 'N Snooze®	Snooze Function (8 hours) Quick Chill Function (2 hours)
Defrost Type	Automatic Defrost
Refrigerant Type	R600a
Door Type	Easy-Clean Euro-Round Doors
Door Handles	Integrated Handles
Door-Swing	Reversible (Factory Standard, Right-Hand Hinge)
Cord Length	77 in.
Interior Shelves	1 Full-Width Removable Shelf
Refrigerator Door Storage	Beverage Can Dispenser (5 cans) Tall Bottle Door Shelf
Leveling	2 Front Adjustable Leveling Feet
Capacity	1.1 cu. ft. Total Capacity

### INSTALLATION REQUIREMENTS

Remove all packing material and tape. Install on a level floor or well-supported counter. Avoid any direct sunlight, heat source, or moisture. This product is designed to be freestanding and must be installed at least 2" from the wall, at least 3/4" to 1" above the floor or carpet, 1" on sides, and 2" on top in order to let the air circulate freely around the unit.

Suite Fridge® hospitality refrigerators are specifically designed for commercial hotel applications only and are not intended for medical or consumer residential applications.

### DIMENSIONS

Width	15 in.
Depth	16.125 in.
Height	20.625 in.
Weight	33 lbs.
Carton Width	16.5 in.
Carton Depth	18.75 in.
Carton Height	21.5 in.
Shipping Weight	36 lbs.
Shipping Cube	3.9 cu. ft.

### ELECTRICAL

A minimum 15 AMP electrical supply is required (20 AMP electrical supply preferred). A time-delay fuse or circuit breaker and separate circuit is recommended.

Electrical Requirements: 115 V | 60 Hz  
Running Amperage: 0.9 A

Absocold, P.O. Box 1545  
Richmond, IN 47375  
Toll-Free: 800-843-3714  
Fax: 765-935-3450  
www.absocold.com  
absocold@absocold.com

**Patent, Copyright and Trademark Information**  
This product is covered by US Patent #7,634,918.  
Other US Patents Pending.