

Absocold® ENERGY STAR® Qualified Compact All-Refrigerator 2.3 cu. ft. Single-Door - Auto-Defrost



ARD244A

Black
Model: ARD244AB21R/L

White
Model: ARD244AW21R/L



FEATURES

Energy	ENERGY STAR® Qualified - Tier III 223 KWH/Yr Energy Consumption 20% less energy than Federal Standard
Defrost Type	Automatic Defrost
Refrigerant Type	R600a Refrigerant
Foaming Agent Type	HFO Foaming
Temperature Control	Full Range Control
Door Type	Easy-Clean Euro-Round Door
Door Handle	Integrated Handle
Door-Swing	Reversible (Factory Standard, Right-Hand Hinge)
Interior Shelves	2 Full-Width Adjustable Wire Shelves
Door Storage	2 Full-Width Shelves Lower Shelf accepts 2-Liter Bottles
Leveling	2 Front Adjustable Leveling Feet
Capacity	2.28 cu. ft. Total Capacity

DIMENSIONS

Height	25 in.
Width	18 1/2 in.
Depth	20 in.
Weight	39 lbs.
Carton Height	26 5/8 in.
Carton Width	20 1/4 in.
Carton Depth	23 3/4 in.
Shipping Weight	44 lbs.
Shipping Cube	7.2 cu. ft.

ELECTRICAL

A minimum 15 AMP electrical supply is required (20 AMP electrical supply preferred). A time-delay fuse or circuit breaker and separate circuit is recommended. 115V, 60 Hz.

Running Amperage: 0.8 AMPS

INSTALLATION REQUIREMENTS

Remove all packing material and tape. Install on a level floor or well-supported counter. Avoid any direct sunlight, heat source, or moisture. This product is designed to be *freestanding* and must be installed at least 2" from the wall, and the cabinet bottom is at least 3/4" to 1" above the floor or carpet, 1" on sides, 2" on top in order to let the air circulate freely around the unit.

Product specifications subject to change without notice



Absocold, P.O. Box 1545, Richmond, IN 47375 Toll-Free: 800-843-3714 • Fax: 765-935-3450
www.absocold.com • absocold@absocold.com