

# Absocold® ENERGY STAR® Qualified Apt-Size Refrigerator/Freezer 4.8 cu. ft. TopFreezer - Frost-Free



## ARD484F

 **Black**  
Model: ARD484FB

 **White**  
Model: ARD484FW



### FEATURES

|                           |  |
|---------------------------|--|
| Energy                    | ENERGY STAR® Qualified - Tier II<br>346 KWH/Yr Energy Consumption<br>15% less energy than Federal Standard |
| Defrost Type              | Frost-Free   |
| Refrigerant Type          | Non-Flammable R134A  |
| Foaming Agent Type        | Non-Flammable 245F   |
| Temperature Control       | Full-Range Control   |
| Door Type                 | Easy-Clean Euro-Round Doors  |
| Door Handles              | Integrated Handles   |
| Door-Swing                | Reversible (Factory Standard, Right-Hand Hinge)  |
| Interior Lighting         | Automatic Refrigerator Light   |
| Crisper                   | 1 Full-Width See-Thru Crisper  |
| Interior Shelves          | 2 Full-Width Adjustable Wire Shelves<br>1 Full-Width Glass Crisper Cover                                   |
| Refrigerator Door Storage | 3 Full-Width Shelves<br>Lower Shelf accepts 2-Liter Bottles  |
| Freezer Interior          | 1 Full-Width Shelf   |
| Freezer Door Storage      | 2 Full-Width Shelves   |
| Leveling                  | 2 Front Adjustable Leveling Feet   |
| Capacity                  | 4.8 cu. ft. Total Capacity<br>3.38 cu. ft. Refrigerator<br>1.37 cu. ft. Freezer                            |

### INSTALLATION REQUIREMENTS

Remove all packing material and tape. Install on a level floor or well-supported counter. Avoid any direct sunlight, heat source, or moisture. This product is designed to be *freestanding* and must be installed at least 2" from the wall, and the cabinet bottom is at least 3/4" to 1" above the floor or carpet, in order to let the air circulate freely around the unit.

### DIMENSIONS

|                 |              |
|-----------------|--------------|
| Height          | 45 3/4 in.   |
| Width           | 18 1/2 in.   |
| Depth           | 22 1/4 in.   |
| Weight          | 76 lbs.      |
| Carton Height   | 47 3/4 in.   |
| Carton Width    | 20 1/4 in.   |
| Carton Depth    | 24 1/2 in.   |
| Shipping Weight | 83 lbs.      |
| Shipping Cube   | 13.7 cu. ft. |

### ELECTRICAL

A minimum 15 AMP electrical supply is required (20 AMP electrical supply preferred). A time-delay fuse or circuit breaker and separate circuit is recommended. 115V, 60 Hz.

Running Amperage: 1.3 AMPS

Product specifications subject to change without notice



Listed by  
Underwriters  
Laboratories.

Absocold, P.O. Box 1545, Richmond, IN 47375 Toll-Free: 800-843-3714 • Fax: 765-935-3450  
www.absocold.com • absocold@absocold.com