

Indoff Hospitality Refrigerator
2.3 cu. ft. Single-Door - Auto-Defrost

Indoff



Available through



IRD230A



Black

Model: IRD230AB20R/L



KEY BENEFITS

- High Efficiency Compressor Cooling
- Slide-out Glass Shelf
- Low Noise Level
- Full-Range Temperature Control
- 2-Liter Bottle Storage

FEATURES

Energy ENERGY STAR® Qualified

Defrost Type	Auto Defrost
Door Type	Easy-Clean Euro-Round Door
Door Handle	Recessed Handle
Door-Swing	Reversible (Factory Standard, Right-Hand Hinge)
Interior Shelves	Slide-Out Glass Shelf
Door Storage	2-Liter Bottle Door Storage

Noise Level Low - 37db

Leveling Adjustable Leveling Feet

Capacity 2.3 cu. ft.

INSTALLATION REQUIREMENTS

Remove all packing material and tape. Install on a level floor or well-supported counter. Avoid any direct sunlight, heat source, or moisture. This product is designed to be *freestanding* and must be installed at least 2" from the wall, and the cabinet bottom is at least 3/4" to 1" above the floor or carpet, in order to let the air circulate freely around the unit.

Product specifications subject to change without notice

DIMENSIONS

Height	25.04 in.
Width	18.66 in.
Depth	17.60 in.
Weight	39.7 lbs.

Carton Height	26.18 in.
Carton Width	20.24 in.
Carton Depth	18.23 in.

Weight 44.10 lbs.

ELECTRICAL

A minimum 15 AMP electrical supply is required (20 AMP electrical supply preferred). A time-delay fuse or circuit breaker and separate circuit is recommended. 115V., 60 Hz.

Running Amperage: 0.9 AMPS



Absocold, P.O. Box 1545, Richmond, IN 47375
Toll-Free: 800-843-3714 • Fax: 765-935-3450
www.absocold.com • absocold@absocold.com

PS-IRD230AB-0120